

Kelin Epoksi Döşeme Eklemleri Yapıştırıcı, renkli su bazlı epoksi kiremit harçından sonra yeni bir yükseltilmiş üründür, sadece renkli su bazlı epoksi kiremit harçının dokusunu korur, ürün performansını yükseltir, ancak inşaatı daha kolay ve daha uygun hale getirir. Yumuşak dokusu, düşük anahtar lüks dekoratif tarzınızı büyük ölçüde gösterir. Renk çeşitleri, dekorasyon yerinizi parlatıyor. Çevre Dostu Epoksi Reçine Alt Baz Kursu, ürününüzün daha su geçirmez, aşınmaya dayanıklı, kalıp geçirmez ve nem geçirmez. Yüksek sıcaklıkta kalsine edilmiş doğal kum, rengi daha doğal ve güzel hale getirir ve asla kaybolmaz. Ayrıca, sararmadan veya sökülmeden takıldıktan sonra porselen kadar parlaktır. Ek olarak, eklem yüzeyi, doğanın kendisi gibi seramik karo için mükemmel görünüyor.

Ürünler **Çin Epoksi Gap Dolgu Tedarikçi** Seramik karo, taş, cam, mozaik kiremit eklemlerinde daha iyi kullanılabilir, banyoda, mutfak, yatak odası vb. Avustralya ortak araştırma ve geliştirme ürünleri daha iyi performans sağlamak ve Çin Bilimler Akademisi ile Stratejik Kalite Kontrol Rehberliği, ürün kalitesini sabitlemek için. Ürünleri **Çin fayans yapıştırıcısı üretici firma** Sizin için en iyi seçimdir.



**Seçtiğiniz renk çeşitleri. Ayrıca özel renkler sağlayın.**

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness

Dark Brown

Reddish Brown

Rock Bslack



Bütün oda boşluk çözümü sağlayın



## Kısa inşaat süreci



01  
Clean the tiles and keep it dry



02  
Polish with tile wax except the glazed tile



03  
Open & Watch, both sides can extruded meanwhile



04  
Screw on the nozzle, put on the grout gun



05  
Inclined cut the top of the nozzle in 45°



06  
Squeeze out 60-80cm long grout in the forepart



07  
Evenly squeeze out the tile agent along the gap



08  
Press the grout with professional glue-press tools



09  
Don't touch in 4-5 hours and remove excess grout then.



10  
Keep the tiles dry in 24 hours

## Profesyonel ortak presleme aracı



Two Component Caulking Gun



02  
Cutter Knife



03  
Pointing trowel



04  
Brush



05  
Forming Stick



06  
Perching Knife



07  
Masking Tape



08  
Stainless Steel Ball



09  
Cleaning Awl

## Şirket avantajı



## Fabrika genel bakış



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

## Sertifika

