

Kelin Epoksi Döşeme Eklemleri Yapıştırıcı, renkli su bazlı epoksi kiremit harçından sonra yeni bir yükseltilmiş üründür, sadece renkli su bazlı epoksi kiremit harçının dokusunu korur, ürün performansını yükseltir, ancak inşaatı daha kolay ve daha uygun hale getirir. Yumuşak dokusu, düşük anahtar lüks dekoratif tarzınızı büyük ölçüde gösterir. Renk çeşitleri, dekorasyon yerinizi parlatıyor. Çevre Dostu Epoksi Reçine Alt Baz Kursu, ürününüzün daha su geçirmez, aşınmaya dayanıklı, kalıp geçirmez ve nem geçirmez. Yüksek sıcaklıkta kalsine edilmiş doğal kum, rengi daha doğal ve güzel hale getirir ve asla kaybolmaz. Ayrıca, sararmadan veya sökülmeden takıldıktan sonra porselen kadar parlaktır. Ek olarak, eklem yüzeyi, doğanın kendisi gibi seramik karo için mükemmel görünüyor.

Ürünler **Çin Epoksi Gap Dolgu Tedarikçi** Seramik karo, taş, cam, mozaik kiremit eklemlerinde daha iyi kullanılabilir, banyoda, mutfak, yatak odası vb. Avustralya ortak araştırma ve geliştirme ürünleri daha iyi performans sağlamak ve Çin Bilimler Akademisi ile Stratejik Kalite Kontrol Rehberliği, ürün kalitesini sabitlemek için. Ürünleri **Çin fayans üreticisi için su geçirmez harc** Sizin için en iyi seçimdir.



Seçtiğiniz renk çeşitleri. Ayrıca özel renkler sağlayın.

Gray 1#

Gray 2#

Gray 3#

Gray 4#

Gray 5#

Gray 6#

Gray 7#

Gray 8#

Gray 9#

Cement Gray

Dull Gray

Silver Gray

Metal Gray

Luxury Silver

Glacier White

Calaeatta

Pearl Gold

Slate Gray

Terra Brown

Greyish Green

Yellow Gray

Soft Khaki

Yellowish Brown

Olive Brown

Brownness


Dark Brown

Reddish Brown

Rock Bslack



Bütün oda boşluk çözümü sağlayın



Kısa inşaat süreci



01
Clean the tiles and keep it dry



02
Polish with tile wax except the glazed tile



03
Open & Watch, both sides can extruded meanwhile




04
Screw on the nozzle, put on the grout gun




05
Inclined cut the top of the nozzle in 45°



06
Squeeze out 60-80cm long grout in the forepart



07
Evenly squeeze out the tile agent along the gap



08
Press the grout with professional glue-press tools



09
Don't touch in 4-5 hours and remove excess grout then.



10
Keep the tiles dry in 24 hours

Profesyonel ortak presleme aracı



Two Component Caulking Gun



02
Cutter Knife



03
Pointing trowel



04
Brush



05
Forming Stick



06
Perching Knife



07
Masking Tape




08
Stainless Steel Ball



09
Cleaning Awl

Şirket avantajı



Fabrika genel bakış



Creaming Machine Line



Testing Machine



Batching Production Line



Cooling Filling



Filling Machine Line



Film-coated Machine



Real Material Stock



Stock

Sertifika

